



Exacting Standards, Just Like Yours, since 1948

Signature Series 1000S Slicer

1000S

Signature Series

1000S Automatic Slicer

High Volume Automatic Slicer With Large 13" Blade

FOUR SPEED PRECISION SLICING WITH THREE STROKE LENGTHS

Finally, a heavy-duty, supermarket quality slicer good enough to be called Univex: The 1000S. Robust construction and superb engineering combine to produce an automatic slicer for those who need heavy slicing production. The slicer uses an oversized, 13" German made, high carbon chrome plated blade that slices from wafer thin up to 0.8". The 13" blade is fully protected, even during cleaning!

A choice of four carriage speeds plus a choice of three stroke lengths lets you optimize your slicing. Built-in slice counter allows you to slice up 99 slices per batch, if you choose. Ultra-smooth anodized aluminum surfaces provide superior glide that reduces operator fatigue and simplifies cleaning. Ideal for high-volume operations, the durable polished aluminum will maintain its matte silver sheen for years to come. Anodized aluminum remote sharpener is easy to use and mounts in seconds. Carriage tilts away from unit for quick and easy cleaning. Extra large feed grip disassembles easily for thorough cleaning. Captive blade cover knob stays attached to unit, no small pieces to lose! Safety features include zero blade exposure during cleaning, carriage system interlock and no volt release. NSF approval and UL listing pending.



13" Blade

Slice from 22 to 57 cuts per minute

½ HP blade motor

Hygienic remote sharpener mounts in seconds

Sanitary polished & anodized aluminum construction

Carriage tilts back for easy cleaning

Slice counter

Warranty

The 1000S carries a one-year, on-site parts and labor warranty against any flaws in materials and workmanship. This period begins date of purchase and, provided the unit is used in accordance with our instructions, is in full effect for one year from that date. Any work performed under this warranty must be performed between the hours of 8:00 a.m. and 5:00 p.m. local time, Monday through Friday. Univex will not pay for overtime charges for work performed other than during normal business hours. Damage incurred in transit or from installation error, accident, alteration or misuse is not covered. Univex shall not be liable for any consequential, compensatory, incidental, or special damages. Contact the Univex service department for any warranty claims.

1000S Automatic 13" Slicer

Signature Series 1000S Slicer

Dimensions

INSTALLED FOOTPRINT:	17 1/2" wide x 22" deep (445 x 550 mm)
REQUIRED OPERATION AREA:	37" wide x 33" deep (940 x 838 mm)
NET WEIGHT:	130 lb. (59 kg)
SHIPPING WEIGHT:	165 lb. (75 kg)
BOX:	39" w x 33" d x 30" h (99 x 84 x 76 cm)
CUBIC MEASURE:	22.3 ft3



Specifications

Slices Per Minute By Speed And Stroke Length			
Stroke Length	4.8" (122 mm)	7.8" (198 mm)	11" (279 mm)
Speed 1	41	27	22
Speed 2	53	37	30
Speed 3	54	43	42
Speed 4	54	57	52

SLICE THICKNESS: Infinitely variable, from 0 to .8" (0 to 20 mm).

MAX PRODUCT SIZE: Carriage will fit product up to 7.5" round or 5" x 9" rectangular in automatic mode.

BLADE: 13" (33 cm) diameter German made, hollow-ground, chrome-plated, high-carbon steel.

MOTOR: 1/2 hp.

ELECTRICAL: 115/60/1-phase. Consult factory for special voltages. Power on indicator light.

CONTROLS: Manual or automatic switch. Membrane keypad with switch for blade and carriage motor, stroke length, speed selectors and counting device. Slice thickness dial.

CONSTRUCTION: Ultra-smooth, polished anodized aluminum chassis, support and feed carriages, gauge plate, blade guard, remnant holder.

ELECTRICAL CORD: Six foot, three-wire power supply cord and plug. Plug not furnished on export models.

HYGIENE / MAINTENANCE: Removable blade guard and remnant holder. Rear product deflector swivels to allow easy access for cleaning. Separate sharpener mounts in seconds.

KNIFE RING GUARD: Permanently mounted knife ring guard protects the non-slicing portion of the knife. With the gauge plate completely closed, the slicer and blade can be cleaned with zero blade exposure.

NO VOLTAGE RELEASE: Prevents inadvertent reactivation of slicer in the event of power interruption. Operator must restart the slicer.

INDICATOR LIGHT: Readily visible light illuminates when knife is rotating.

TILTING CARRIAGE SYSTEM: With thickness dial set to "0", carriage tilts back easily for cleaning. Carriage system interlock does not allow gauge plate to be opened with carriage tilted for cleaning.

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

univex